




Jack Stands

Jackstand
Model :



Very stable base assembly



Wirepak rotatable
cap tension brush



Features

- Motorized and non-motorized wyrepak rotatable caps
- Extremely maneuverable
- Very stable base assembly
- Wyrepak rotatable cap tension brush
- 2000 lbs (907 kg); and 2700 lbs (1225 kg) units available
- Shafts are supplied to meet customers applications

JACK STANDS			
Model	Lifting Capacity 18" (460 mm) Load Center	Maximum Reel Width	Maximum Reel Bore
PJ-E- 2000 PJ- EM-2000	2000 lbs (907 kg)	30" (760 mm)	5" (127 mm) 5"/8" (127mm/203mm)
PJ-E- 2700 PJ- EM-2700	2700 lbs (1225 kg)	30" b (760mm)	5"/8" (127mm/203mm) 5"/8" (127mm/203mm)

Industrial Duty Lift Trucks are available with manual hydraulic lifts or electric lifts. Each lift speed is approximately 4" (102 mm) per second. Each jack stand has a 1-1/4" (32 mm) or 1-1/2" (38 mm) sleeve diameter arbor shaft with a 5" (127 mm) or 3" (76 mm) sleeve for standard drawing reels, and one Wyrepak rotatable cap tension brush. All jack stands are painted federal safety orange and include a screen for operator safety.